



Amphel pH Electrodes with Replaceable Battery - General Purpose pH Electrodes

| Code | Body | Junction | Electrolyte | Glass Type | Temperature | Max Pressure | Connector | Cable |
|-----------|------|----------|-------------|------------|-------------|--------------|-----------|-------|
| HI6291005 | PEI | cloth | gel | GP | -5 to 70 °C | 3 bar | BNC | 5 m |

Amphel pH Electrodes with Replaceable Battery - High Temperature pH Electrodes

| Code | Body | Junction | Electrolyte | Glass Type | Temperature | Max Pressure | Connector | Cable |
|-----------|-------|----------|-------------|------------|-------------|--------------|-----------|-------|
| HI8299505 | glass | PTFE | polymer | HT | 0 to 100 °C | 3 bar | BNC | 5 m |



Amphel pH Electrodes with Internal Battery

| Code | Body | Junction | Electrolyte | Glass Type | Temperature | Max Pressure | Connector | Cable |
|-----------|------|----------|-------------|------------|-------------|------------------|-----------|-------|
| HI2910B | PEI | cloth | gel | GP | -5 to 70 °C | 3 bar (43.5 psi) | BNC | 1 m |
| HI2910B/5 | PEI | cloth | gel | GP | -5 to 70 °C | 3 bar (43.5 psi) | BNC | 5 m |
| HI2911B/5 | PEI | PTFE | polymer | GP | -5 to 80 °C | 3 bar (43.5 psi) | BNC | 5 m |

Amphel ORP Electrodes with Replaceable Battery

| Code | Body | Junction | Electrolyte | PIN Type | Temperature | Max Pressure | Connector | Cable |
|-----------|------|----------|-------------|----------|-------------|------------------|-----------|-------|
| HI6293005 | PEI | cloth | gel | platinum | -5 to 80 °C | 3 bar (43.5 psi) | BNC | 5 m |
| HI6493005 | PEI | cloth | gel | gold | -5 to 80 °C | 3 bar (43.5 psi) | BNC | 5 m |

Amphel ORP Electrodes with Internal Battery

| Code | Body | Junction | Electrolyte | PIN Type | Temperature | Max Pressure | Connector | Cable |
|-----------|------|----------|-------------|----------|-------------|------------------|-----------|-------|
| HI2930B/5 | PEI | cloth | gel | platinum | -5 to 80 °C | 3 bar (43.5 psi) | BNC | 5 m |
| HI2931B/5 | PEI | PTFE | gel | platinum | -5 to 80 °C | 3 bar (43.5 psi) | BNC | 5 m |