#### HI97701

# Free Chlorine Portable Photometer

# • Advanced LED optical system

- · Innovative optical design that utilizes a reference detector and focusing lens to eliminate errors from changes in the light source and from imperfections in the glass cuvette.
- · LEDs have a much higher luminous efficiency, providing more light while using less power. They also produce little heat, which could otherwise affect electronic stability.

# CAL Check™

· Validate instrument performance at any time using CAL Check cuvettes made with NIST traceable standards. The CAL Check screen guides the user step-by-step through the validation process and user calibration.

### • On-screen tutorial mode with animations

- · Guides users step-by-step through the measurement process
- Waterproof and floating IP67 case
- Unit of measure is displayed along with reading

#### · Built-in timer

· Built-in reaction timer that ensures consistency between tests.

# • Error messages on display

Alerts to problems including no cap, high zero, and standard too low

- · Displays the last calibration date.
- · Auto logging
- · Battery status indicator
- · Auto-shut off



Specifications		HI97701 Free Chlorine
	Range	0.00 to 5.00 mg/L

Measurement	Range	0.00 to 5.00 mg/L (as Cl <sub>2</sub> )
	Resolution	0.01 mg/L
	Accuracy @25°C (77°F)	±0.03 mg/L ±3% of reading at 25 °C
	Method	adaptation of US EPA method 330.5, DPD Colorimetric method
Measurement System	Light Source	light emitting diode
	Bandpass filter	525 nm
	Bandpass filter bandwidth	8 nm
	Bandpass filter wavelength accuracy	±1.0 nm
	Light Detector	silicon photocell
	Cuvette type	round 24.6 mm diameter (22 mm inside)
Additional Specifications	Auto logging	50 readings
	Display	128 x 64 pixel B/W LCD with backlight
	Auto-off	after 15 minutes of inactivity (30 minutes before a READ measurement)
	Battery type / Life	alkaline 1.5 V AA (3) / > 800 measurements (without backlight)
	Environment	0 to 50°C (32 to 122°F); 0 to 100% RH, non-serviceable
	Dimensions	142.5 x 102.5 x 50.5 mm (5.6 x 4.0 x 2.0")
	Weight	380 g (13.4 oz.)

HI97701 is supplied with sample cuvettes (2), sample caps (2), plastic stoppers (2), 1.5V AA batteries (3), instrument quality certificate, and instruction manual.  ${\sf CAL\,Check\,standards\,and\,testing\,reagents\,sold\,separately}$ 

# Ordering Information

HI97701C includes photometer, CAL Check standards, sample cuvettes (2), sample caps (2),  $plastic \, stoppers \, (2), 1.5 \, V \, AA \, batteries \, (3), \, cuvette \, wiping \, cloth, \, scissors, CAL \, Check \, standard \, (3), \, cuvette \, wiping \, cloth, \, scissors, \, CAL \, Check \, standard \, (3), \, cuvette \, wiping \, cloth, \, scissors, \, can be considered as a constant of the con$  $certificate, instrument \, quality \, certificate, instruction \, manual, and \, HI7101412 \, rigid \, carrying \, case.$ Reagents sold separately

# Reagents and Standards

HI97701-11 CAL Check standard cuvettes for free and total chlorine

HI93701-01 free chlorine powder reagent (100 tests) HI93701-03 free chlorine powder reagent (300 tests) HI93701-F free chlorine liquid reagent (300 tests)

HI97701