HI98501 Checktemp®

Digital Thermometer

with Stainless Steel Penetration Probe

- Large display
 - The large display features a wide temperature range and optimal viewing angle.
- User selectable °C or °F
- CAL Check™
 - Automatically verifies calibration at startup
- IP65 water resistant protection
- Use as a tool for control in HACCP analysis
- AISI 316 stainless steel penetration probe

Checktemp® Digital Thermometer is a great choice for easy operation with clear digits and better accuracy over a wide range.

Measure temperature without fear of breakage or condensation. This compact meter with a direct probe is ideal for taking quick temperature measurement in semisolids and liquids.

The sharp-tip probe of the Checktemp® easily penetrates semi-solid products making routine temperature checks simple and quick for both incoming and outgoing goods. Checktemp is the ideal instrument for measuring temperature according to HACCP requirements.

Checktemp is provided with Hanna's unique CAL Check™ function for accurate measurements every time. The Checktemp® implements a CAL Check upon startup and reports the status as "-0-" or "Err".



Select between °C or °F measurement in one tester

www.hannainst.com







Specifications °C

Specifications	
Range	-50.0 to 150.0°C
Resolution	0.1°C (-50.0 to 150.0°C)
Accuracy	±0.2°C (-30 to 120°C) ±0.3°C (outside: -50.0 to -30.0°C and 120.0 to 150.0°C)
Probe	fixed, stainless steel probe; 106 x ø 3.6 mm (penetration)
Battery Type / Life	CR2032 Li-ion / approximately 2000 hours of continuous use
Auto Off	8 min (default), 60 min or OFF
Environment	-30 to 50°C (-22 to 122°F); IP65
Dimensions	50 x 185 x 21 mm (2 x 7.3 x 0.9")
Weight	50 g (1.8 oz.)
Ordering Information	HI98501 (Checktemp®) is supplied with penetration probe, protective cap, battery, and instructions.
Battery Type / Life Auto Off Environment Dimensions Weight Ordering	CR2032 Li-ion / approximately 2000 hours of continuous use 8 min (default), 60 min or OFF -30 to 50°C (-22 to 122°F); IP65 50 x 185 x 21 mm (2 x 7.3 x 0.9") 50 g (1.8 oz.) HI98501 (Checktemp®) is supplied with penetration probe, protective cap,



CAL Check™

Automatically verifies calibration at startup and alerts the user to the calibration status



Easy battery change

Easily replace the battery with a twist-off cover

Save battery life with auto-off feature

With the auto-off feature, select from 8 min., 60 min., or disable the feature



Protective probe sleeve included

Protects the probe when not in use

